


## Yuvarlak Tip - İzoleli Kablo Uçları ( DIN 46237 ) / ( PVC & Standart Giriş )



**Malzeme** : Bakır (E-Cu), Kalay kaplı  
**İzolasyon** : PVC  
**Çalışma Sıcaklığı** : Maksimum 75° 600 Volt



Ürün Kodu	Kablo Kesiti mm <sup>2</sup>	Civata Ölçüsü	Ebatlar (mm)							Ambalaj Miktarı (Ad)	Ambalaj Ağırlığı (~gr)
			d2	d3	l	d1	d4	a	S		
YK-301	0,50 - 1,50 mm <sup>2</sup>	M3	3,2	6,0	16,0	1,6	4,0	10,0	0,8	200	182
YK-401		M4	4,3	8,0	17,0	1,6	4,0	10,0	0,8	200	206
YK-501		M5	5,3	10,0	18,0	1,6	4,0	10,0	0,8	200	238
YK-601		M6	6,5	10,0	18,0	1,6	4,0	10,0	0,8	200	255
YK-801		M8	8,4	14,0	22,0	1,6	4,0	10,0	0,8	200	324
YK-302	1,50 - 2,50 mm <sup>2</sup>	M3	3,2	6,0	16,0	2,3	4,5	10,0	0,8	200	202
YK-402		M4	4,3	8,0	17,0	2,3	4,5	10,0	0,8	200	224
YK-502		M5	5,3	10,0	19,0	2,3	4,5	10,0	0,8	200	269
YK-602		M6	6,5	11,0	21,0	2,3	4,5	10,0	0,8	200	297
YK-802		M8	8,4	14,0	22,0	2,3	4,5	10,0	0,8	200	346
YK-1002	4,00 - 6,00 mm <sup>2</sup>	M10	10,5	15,0	22,0	2,3	4,5	10,0	0,8	100	253
YK-1202		M12	13,0	18,0	25,0	2,3	4,5	10,0	0,8	100	200
YK-406		M4	4,3	8,0	21,0	3,6	6,3	13,0	1,0	100	205
YK-506		M5	5,3	10,0	22,0	3,6	6,3	13,0	1,0	100	223
YK-606		M6	6,5	11,0	22,5	3,6	6,3	13,0	1,0	100	249
YK-806	4,00 - 6,00 mm <sup>2</sup>	M8	8,4	14,0	26,0	3,6	6,3	13,0	1,0	100	290
YK-1006		M10	10,5	18,0	28,0	3,6	6,3	13,0	1,0	100	351
YK-1206		M12	13,0	18,0	28,0	3,6	6,3	13,0	1,0	50	172