


## İzoleli Kablo Yüksükleri Alman Renk Normu ( DIN 46228 )



**Standart** : DIN 46228  
**Malzeme** : Bakır (E-Cu), Kalay kaplı  
**İzolasyon** : Naylon  
**Çalışma Sıcaklığı** : Maksimum 105° 600 Volt

Ürün Kodu	Renk	Kablo Kesiti mm <sup>2</sup>	Ebatlar (mm)							Ambalaj Miktarı (Ad)	Ambalaj Ağırlığı (~gr)
			F	L	W	B	D	C			
UY-2005		Turuncu	0,50 mm <sup>2</sup>	8,0	14,0	2,6	6,0	1,3	1,0	500	64
UY-2007		Beyaz	0,75 mm <sup>2</sup>	8,0	14,0	2,8	6,3	1,5	1,2	500	72
UY-2010		Sarı	1,00 mm <sup>2</sup>	8,0	14,0	3,0	6,3	1,7	1,4	500	75
UY-2015		Kırmızı	1,50 mm <sup>2</sup>	8,0	14,0	3,5	6,3	2,0	1,7	500	108
UY-2015/18		Kırmızı		18,0	24,0	3,5	6,3	2,0	1,7	500	150
UY-2025		Mavi	2,50 mm <sup>2</sup>	8,0	15,0	4,2	7,4	2,5	2,2	500	133
UY-2025/12		Mavi		12,0	18,0	4,2	7,4	2,5	2,2	500	167
UY-2025/18		Mavi		18,0	24,0	4,2	7,4	2,5	2,2	250	119
UY-2040		Gri	4,00 mm <sup>2</sup>	10,0	17,0	4,8	7,4	3,2	2,8	250	119
UY-2040/12		Gri		12,0	20,0	4,8	7,4	3,2	2,8	250	125
UY-2040/18		Gri		18,0	26,0	4,8	7,4	3,2	2,8	250	150
UY-2060		Siyah	6,00 mm <sup>2</sup>	12,0	20,0	6,3	8,5	3,9	3,5	250	179
UY-2060/18		Siyah		18,0	26,0	6,3	8,5	3,9	3,5	200	177
UY-2100		Bej	10,00 mm <sup>2</sup>	12,0	22,0	7,6	8,8	4,9	4,5	100	109
UY-2100/18		Bej		18,0	28,0	7,6	8,8	4,9	4,5	100	124
UY-2160		Yeşil	16,00 mm <sup>2</sup>	12,0	24,0	8,8	10,0	6,2	5,8	100	138
UY-2160/18		Yeşil		18,0	28,0	8,8	10,0	6,2	5,8	100	157
UY-2250		Kahve	25,00 mm <sup>2</sup>	16,0	28,0	11,2	12,0	7,7	7,3	50	125
UY-2350		Bej	35,00 mm <sup>2</sup>	16,0	30,0	12,7	14,0	8,7	8,3	50	140
UY-2500		Zeytuni	50,00 mm <sup>2</sup>	20,0	36,0	15,0	16,0	10,9	10,3	50	168