


## İzoleli Kablo Yüksükleri Fransız Renk Normu ( DIN 46228 )



**Standart** : DIN 46228  
**Malzeme** : Bakır (E-Cu), Kalay kaplı  
**İzolasyon** : Naylon  
**Çalışma Sıcaklığı** : Maksimum 105° 600 Volt

Ürün Kodu	Renk	Kablo Kesiti mm <sup>2</sup>	Ebatlar (mm)							Ambalaj Miktarı (Ad)	Ambalaj Ağırlığı (-gr)
			F	L	W	B	D	C			
UY-3003		Pembe	<b>0,30 mm<sup>2</sup></b>	8,0	12,4	1,9	4,4	1,1	0,8	500	50
UY-3005		Beyaz	<b>0,50 mm<sup>2</sup></b>	8,0	14,0	2,6	6,0	1,3	1,0	500	64
UY-3007		Mavi	<b>0,75 mm<sup>2</sup></b>	8,0	14,0	2,8	6,3	1,5	1,2	500	72
UY-3010		Kırmızı	<b>1,00 mm<sup>2</sup></b>	8,0	14,0	3,0	6,3	1,7	1,4	500	75
UY-3015		Siyah	<b>1,50 mm<sup>2</sup></b>	8,0	14,0	3,5	6,3	2,0	1,7	500	108
UY-3015/10		Siyah		10,0	16,0	3,5	6,3	2,0	1,7	500	116
UY-3015/18		Siyah		18,0	24,0	3,5	6,3	2,0	1,7	500	150
UY-3025		Gri	<b>2,50 mm<sup>2</sup></b>	8,0	15,0	4,2	7,4	2,5	2,2	500	133
UY-3025/12		Gri		12,0	18,0	4,2	7,4	2,5	2,2	500	167
UY-3040		Turuncu	<b>4,00 mm<sup>2</sup></b>	10,0	17,0	4,8	7,4	3,2	2,8	250	119
UY-3060		Yeşil	<b>6,00 mm<sup>2</sup></b>	12,0	20,0	6,3	8,5	3,9	3,5	250	177
UY-3100		Kahve	<b>10,00 mm<sup>2</sup></b>	12,0	22,0	7,6	8,8	4,9	4,5	100	109
UY-3160		Fildişi	<b>16,00 mm<sup>2</sup></b>	12,0	24,0	8,8	10,0	6,2	5,8	100	138
UY-3250		Siyah	<b>25,00 mm<sup>2</sup></b>	16,0	28,0	11,2	12,0	7,7	7,3	50	125
UY-3350		Kırmızı	<b>35,00 mm<sup>2</sup></b>	16,0	30,0	12,7	14,0	8,7	8,3	50	141
UY-3500		Mavi	<b>50,00 mm<sup>2</sup></b>	20,0	36,0	15,0	16,0	10,9	10,3	50	168
UY-3700		Sarı	<b>70,00 mm<sup>2</sup></b>	20,0	37,0	16,0	17,0	14,3	13,5	50	270